

Condenser Fan and Direct Drive Blower

APPLICATIONS:

PSC motors for condensing unit and blower applications.
Built in Princeton, Indiana.

FEATURES:

RESCUE Liberty Condenser Fan Multi-Horsepower Motors

- **Horsepower:** 1/3–1/6 HP
- **Enclosure:** Totally Enclosed Air Over (TEAO)
- **Speed:** See Below
- **Rated Voltages:** 208–230 Volts
- **Ambient Rating:** 70°C (158°F)
- **Capacitor:** 5.0 or 7.5mfd (*included*)
- **Mounting:** All Position Mounting, Rheem† Side Shell Holes include Rheem† and Trane† Endshield Mounting Holes
- **Warranty:** Two-year limited warranty from date of installation

RESCUE Liberty Furnace and Air Handler Direct Drive Blower Multi-Horsepower Motors

- **Horsepower:** 1/2–1/6 HP
- **Enclosure:** Open Air Over (OAO)
- **Speed Range:** 1075 RPM
- **Rated Voltages:** 115 and 208–230
- **Ambient Rating:** 60°C (140°F)
- **Capacitor:** Compatible with 370V (*not included*)
- **Mounting:** Thru-Bolts, Rheem† Shell Holes, or Belly Band; Extended Mounting Studs; 2.5" Dia. Hub Rings Included
- **Warranty:** Two year limited warranty from date of installation

RESCUE Liberty Condenser Fan Multi-Horsepower Motor

HP	RPM	Voltage	Catalog Number	Speed	Cap MFD	Amps	Bearing	Shaft Length	Total Length
1/3–1/6	1075	208-230	US5462H	2	5	2.6/1.8	BALL	4.5	9.6
1/3–1/6	825	208-230	US5464H	2	7.5	1.9/1.2	BALL	4.5	10.3

RESCUE Liberty Furnace and Air Handler Direct Drive Blower Multi-Horsepower Motor

HP	RPM	Voltage	Catalog Number	Speed	Cap MFD	Amps	Bearing	Shaft Length	Total Length
1/2–1/6	1075	115	US5460	4	12.5-7.5	7.3	SAB	5.5	10.8
1/2–1/6	1075	208-230	US5461	4	10-5	3.6	SAB	5.0	10.3